



## Solar Photovoltaic Modules

### NEASE Solar Photovoltaic Module Specification Data

Module Type	12V/120WP	12V/125WP
Max. Power	120WP	125WP
Cell Type	Poly/Mono Crystalline Silicon Solar Cells	
No. Of Cell	36 Cell	
Max. System Voltage	1000V	
Power Tolerance	± 3%.	
Surface Maximum Load Capacity	60m/s(200kg/sq.m)	
Weight	9.70 kg	
Glass Dimensions	1350mm X 670 mm X 3.2 mm	
Electrical Characteristic		
Open Circuit Voltage(Voc)	21.5V	21.5V
Short Circuit Current(isc)	7.30A	7.59A
Max. Power Voltage(Vmax)	17.5V	17.5V
Max. Power Current(imax)	6.87A	7.10A
Temp Coefficiencies Of Isc(%)	20µA/°C/Cell area/C_P	
Temp Coefficiencies Of Voc(%)	-2.2mv/°C/C_S	
Temp Coefficiencies Of Pm (%)	-0.44%/°C	
Cell Efficiency (%)	>15%	
Module Efficiency(%)	>13%	>13.5%
Operating Temperature	-40 to +85°C	



### Features and Benefits

- ❖ Cells are laminated with EVA, TPT and tempered glass ensuring long life and the most stringent safety requirements For High voltage operation.
- ❖ Anodized aluminum frame with convenient mounting slots.
- ❖ Nominal 6VDC/ 12V DC / 20V / 24V DC for standard output.
- ❖ We are specialized in 18, 36, 54, 60, 72 cells solar modules.
- ❖ We are specialized in making black and transparent back-sheet solar module as well.
- ❖ Withstand high wind pressure and snow load.
- ❖ Output power tolerance of ± 3%.
- ❖ High efficiency solar cells.



\*Conditions:(STC):Irradiance:1000W/m<sup>2</sup>,spectral distribution AM1.5,Cell temperature:25°C

### Module Dimensions



### Certification



**MNRE**  
Channel  
Partner



**\* NEASE reserves the right to amend the above specification without prior notice.**

## NEETY EURO-ASIA SOLAR ENERGY

B/4/1 GIDC Electronics Estate Sector - 25 Gandhinagar - 382024 Gujarat , India

Tel : +91-79-23287395,23287396 Fax : +91-79-23287394

Email: [sales@nease.in](mailto:sales@nease.in) & [info@nease.in](mailto:info@nease.in)

Web Site: [www.nease.in](http://www.nease.in)